

# INSPIRATION/2 770

built-in hood



## EVO ENGINE



Alternative Current motor with reduced noise level at the lowest speeds

## BOOSTER FUNCTION



Superior and timed hood performance over a maximum period of 6 minutes

## PERIPHERAL SUCTION



The peripheral openings allow all vapours and fumes to be captured by optimizing the efficiency of the hood.

## HIGH PERFORMANCE FILTER (optional)



Efficient and economical solution, the high-performance filters are dishwasher-safe and self-regenerating. They have a lifespan of approximately 3 years

## CONTROLS

Control type	Electronics backlit
Number of speeds	3 + boost

## ENERGY EFFICIENCY

Annual Efficiency Consumption (AEC) kWh/a	53,5		
Energy Efficiency Class	A		
Air flow (m <sup>3</sup> /h)	<i>Min</i>	<i>Max</i>	<i>Boost</i>
	308	594	712
Airborne acoustical A-weighted sound Power Emission (dB)	<i>Min</i>	<i>Max</i>	<i>Boost</i>
	49	66	70

## FILTRATION

Grease filter	Aluminium
Number of grease filters	1
Charcoal filter	Optional ( x1)

## PERFORMANCES

	Min	Mid	Max	<i>Boost</i>
Capacity point suction IEC (m <sup>3</sup> /h)	308	433	594	712
Power (Watts)	170	210	248	255
Pressure (BP)	425	484	515	530
Noise level dB (A)	49	59	66	70
Noise pressure (dB(A))	43	53	60	64

## LIGHT

Light	LED Bar
Number of lamps and power + Kelvin	2 x 4 W (4000K)
Dimmer	No

# INSPIRATION/2 770

## TECHNICAL DATA

Frequency (Hz)	50 – 60
Fuse (A)	10
Voltage (V)	220 – 240
Electrical wire	Included

## INSTALLATION

Mode	Ducting or recycling
Installation without chimney	N/A
Installation height (min, mm)	650 (electric plate) 530 (gas plate)
Outlet diameter (mm)	Ø150

## DIMENSIONS & WEIGHTS

Dimensions of the product without chimney (W x H x D - mm)	259 x 770 x 320
Carton dimension (W x H x D - mm)	500 x 860 x 420
Chimney height min-max (mm)	-
Gross weight (kg)	11,0
Net weight (kg)	9,0

