FOTILE

1108000807570

■ 安裝要求　Installation Requirements

1. 臺面開孔尺寸：960*480*R5mm，詳見圖1所示；
2. 臺面和櫥櫃要求：櫥櫃深度（不含門板）≥540mm，櫥櫃內壁寬度≥965mm，臺面深度≥600mm，臺面至地面高低≥800mm，詳見圖1和圖2所示；
3. 進水/插座要求：冷、熱角閥距離地面高度350mm（左熱右冷），位于插座下方，水槽側。角閥上方距離地面高度450mm，布置1.5mm²以上電綫及10A的單相三孔插座，且必須可靠接地。詳見圖3所示；
4. 排水要求：下水管高度≤350mm，口徑≥50mm，位于水槽一側，詳見圖3所示；如果爲墻排，墻排在左側時，需選型右款機型；墻排在右側時，需選型左款機型，避免與整機嵌入干涉，詳見圖4所示；
5. 水槽一側鉸鏈要求：鉸鏈距離臺面≥210mm，避免鉸鏈與整機嵌入干涉，詳見圖3所示；
6. 水槽龍頭板厚度30mm，請確保水龍頭/净水機固定螺栓≥35mm。

1. Countertop opening size: 960*480*R5 mm. See Figure 1 for details;
2. Countertop and cabinet requirements: Cabinet depth (excluding door panel) ≥ 540 mm, cabinet inner wall width ≥ 965 mm, countertop depth ≥ 600 mm, height from countertop to floor ≥ 800 mm. See Figures 1 and 2 for details;
3. Water inlet/socket requirements: Cold and hot angle valves should be 350 mm above the floor (hot on the left, cold on the right), located below the socket on the sink side. The angle valve should be 450 mm above the floor, with at least 1.5 mm² of wiring and a 10A single-phase three-prong socket, and must be reliably grounded. See Figure 3 for details;
4. Drainage requirements: Drain pipe height ≤ 350 mm, caliber ≥ 50 mm, located on the sink side. See Figure 3 for details; If wall drainage is used, select the Right-Hand (RH) model if the wall drain is on the left; select the Left-Hand (LH) model if the wall drain is on the right to avoid interference with the embedded machine. See Figure 4 for details;
5. Hinge requirements on sink side: Hinge distance from countertop ≥ 210 mm to avoid interference with the embedded machine. See Figure 3 for details;
6. Sink faucet panel thickness should be 30 mm. Please ensure the faucet/purifier mounting bolt is ≥ 35 mm.



圖1
Figure 1



圖2
Figure 2



圖3
Figure 3

■ 產品尺寸　Product dimensions





■ 尺寸要求　Dimensional Requirements

型號 Model	開孔尺寸（mm） Opening size（mm）			外形尺寸（mm） Overall dimensions（mm）			櫥櫃內壁尺寸（mm） Interior wall dimension of cupboard（mm）		
SD2F-P7 SD2F-P7L	長度 Length	寬度 Width	R 角 R angle	長度 Length	寬度 Width	高度 Height	長度 Length	寬度 Width	高度 Height
	960	480	5	985	505	650	≥965	≥520	≥800

■ 裝箱單　Packing List

使用説明書 Instructions Manual		1份 1 Copy	安裝説明書 Installation Instructions		1份 1 Copy
整機 Main Unit		1臺 1 Unit	排水管組件 Drain Pipe Assembly		1套 1 Set
菜籃 Vegetable Basket		1套 1 Set	下水器 Drain Fitting		1個 1 Piece
碗架組件 Bowl rack component		1套 1 Set	快速操作指南 Quick Start Guide		1份 1 Copy
橡膠管 Rubber hose		1個 1 Piece	進水連接管 Inlet Hose		1個 1 Piece
三通接頭 T-junction		1個 1 Piece	進水連接管轉接頭 Inlet Hose adapter		1個 1 Piece
溢水座−排氣三通連接管 Connecting hose of the overflow seat-exhaust tee		1個 1 Piece			

■ 建議安裝工具（需用户自備）
Recommended installation tools（Need to be prepared by the user）

（請根據實際安裝環境來配置相應工具）
(please use appropriate tools according to actual installation environment)

材料 Material	規格 Specification	數量 Quantity	材料 Material	規格 Specification	數量 Quantity
	PC-1250 Single Stroke Plastic Pipe Cutter	1		Glue gun + water-proof and mildew proof glass cement	1
	Regular Flat Head screwdriver	1		Glass cement scraper	1
	Self Adjusting Groove Joint Pliers	1		Tape Measure	1
	Lock Nut Wrench	1			



第一步：開箱，將機器豎直放置在紙板上。
Step 1: Unpack the machine and place it upright on the cardboard.



第二步：安裝排水管組件和下水器，按照如圖所示放置好各零件，最后將螺母擰緊。
注意：將厚的密封墊置于排水管組件塑殼的上方，薄的密封墊置于水槽落水孔上方。

Step 2: Install the drain pipe assembly and the drain fitting. Arrange all parts as illustrated, then securely tighten the nut.
Note: Place the thick sealing gasket above the plastic housing of the drain pipe assembly, and the thin sealing gasket above the sink drain opening.



第三步：C接口處先插入溢水座−排氣三通連接管，將排水管組件上的各分支水管與洗碗機上的各接口按字母對應連接。
注意：安裝洗碗機排水管時，需先將該接口上的卡扣拆下，排水管接入該接口后再用卡扣卡緊；門鎖溢水孔A與排水管組件A接口需使用橡膠管連接。

Step 3: Insert Connecting hose of the overflow seat-exhaust tee into the C interface first, Connect each branch hose of the drain pipe assembly to the corresponding port on the dishwasher by matching their letter markings.
Note: When installing the dishwasher drain pipe, first remove the clip from the port, insert the pipe into the port, then re-secure the clip; The overflow hole A of the door lock and port A of the drain pipe assembly must be connected using a rubber hose.



第四步：安裝水龍頭。
Step 4: Install the faucet.



第五步：臺面做好清潔，沿安裝孔邊緣打防水硅膠，確保連續不斷點。
Step 5: Clean the countertop thoroughly, apply waterproof silicone along the edge of the installation hole, and ensure a continuous coverage.

第六步：戴上防護手套，將洗碗機由上往下嵌入櫥櫃。
注意：1、抬水槽洗碗機時禁止手持水龍頭，以免水龍頭松脱導致漏水。
2、水槽洗碗機放入臺面時，請保持四周受力均勻，以免單側放在一個受力點上導致臺面開裂。
Step 6: Put on protective gloves and embed the dishwasher into the cabinet downward until full engagement.
Note: 1. Do not hold the faucet with hands when moving the sink dishwasher, otherwise water leakage may happen due to loosening of the faucet.
2. When putting the sink dishwasher into the mounting opening, make sure its rim withstand a uniform stress to avoid cracking of the countertop due to non-uniform stresses.

第七步：將進水管與洗碗機進水閥（E接口）擰緊，另一端接入冷水（建議您先將轉接頭旋緊于水閥上，然后再接進水管）。正確連接好水龍頭的冷、熱水管。
Step 7: Tighten the inlet hose to the dishwasher inlet valve (E port), and connect the opposite end to cold water (it is recommended to first tighten the adapter to the water valve, then connect the inlet hose). Correctly connect the cold and hot water pipes to the faucet.

注：本產品有配三通接頭，若安裝時水閥接口不够，可使用該三通。
Note: This product is provided with a three-way fitting. If the water valve ports are insufficient during installation, the three-way fitting may be used for installation.

第八步：將排水管組件尾端提高至臺面，水槽下水器上方蓋上下水器蓋子，向水槽內注入水，水位高于水槽溢水口，然后拿掉下水器蓋子，檢查確保排水管組件各接口不漏水。
Step 8: Lift the end of the drain pipe assembly to the countertop level, cover the sink drain fitting with its lid, fill the sink with water until the water level is above the overflow outlet, then remove the drain fitting lid and verify all drain pipe assembly connections are leak-free.



第九步：沿產品邊沿打上防水透明硅膠，確保與臺面密封。將排水管尾端接入下水管道，接口處做好密封，并將洗碗機接好電源。
Step 9: In order to guarantee sealing on the countertop, apply waterproof and transparent silica gel along the edge of the product.Connect the drain pipe end to the building's main drainage conduit, seal the junction properly, then connect the dishwasher to the power supply .



第十步：安裝噴淋臂。從包裝上泡沫上拿出噴淋臂，將噴淋臂對准噴淋臂安裝孔，向下按壓，當聽到“咔噠”聲后，噴淋臂即安裝完成。關于噴淋臂的拆裝、日常清潔保養説明書有做説明，請詳細保管好產品使用説明書及安裝指南。
Step 10: Install the spray arm. Take the spray arm out of the foam packaging, align it with the mounting hole, and press downward. Once a "click" sound is heard, the spray arm is successfully installed. For details on the disassembly, assembly, daily cleaning, and maintenance of the spray arm, please refer to the instruction manual. Kindly keep the product user manual and installation guide properly.