空氣淨化技術 AIR CARE TECHNOLOGY

採用頂尖空氣淨化技術,達到空氣淨化功能:防塵及殺菌。
The top technology of air care is a combination of dust elimination and sterilization.



防塵功能: Dust Elimination

高效能防塵過濾網可有效過濾PM2.5粒子、一些微細致敏原、香煙煙霧和黴菌, 淨化高達90%,減少空氣中的懸浮粒子的 累積,避免直接吸入肺部,對人體造成很大的傷害。

Effectiveness in filtering PM2.5, allergens, smoke and mold allergy, up to 90%. Reducing the accumulation of suspended particles, to avoid the direct inhalation and cause the harm to human being.

殺菌功能: Sterilization

測試結果顯示可在1小時內去除90%以上的空氣中的金黃葡萄球菌,金黃葡萄球菌大多通過觸碰到空氣中的皮屑或別人的皮膚而感染,主要影響兒童。它會造成膿胞腫,膿包症,蜂窩性組織炎。如果細菌經由血管流至骨頭、肺部或心臟,就有可能導致危及生命的感染。

The test result shows that the sterilization rate of staphylococcus aureus is above 90% in 1 hour. Staphylococcus aureus can spread through the air on skin scales (dust), by skin to skin contact or by touching contaminated surfaces, mainly affects children. Symptoms of some common skin and soft tissue staph infections include boils, impetigo and cellulitis. If the bacteria enters your bloodstream and then on to bones, lungs or heart. These can lead to more serious infection, sometimes life-threatening.

*多功能浴室淨·暖機的各項表現會因應實際環境而不同。
The performance of the bathroom heater varies depending on the actual environment.

結構圖 STRUCTURE

紅色: 故障指示, 濾網更換提示

宣州北纽/// 中域市场。

防過熱、防爆裂

High Quality Tempered Glass Panel: Fire retardant material.

Fire retardant material, anti-overheating, anti-bursting.

陶瓷PTC* 加熱組件:

防過熱設計, 保護加熱器, 避免 燃燒風險

Ceramic PTC* Heating Components: Anti-overheating design

Anti-overheating design protects the heater, avoids burning.

金屬外殼:

及時散熱且不易變形, 牢固耐用

Metal Cover:

Heat dissipation, robust and durable.

*Positive Temperature Coefficient 正溫度系數

Orange: Hot Wind White: Cool Wind Red: Error indication, filter replacement reminder

防塵濾網

橙色: 熱風; 白色: 涼風;

Status Indicator:

累計使用約6個月,顯示濾網警報,可輕鬆拆卸清洗

Dust Filter

LED red light indicates to clean the dusk filter after using around 6 months.

過流保險絲:

電路發生故障,或其他原因造成短路可立即切斷電源

Current Fu

Cut off the power if there is any short circuit or error.

6 SAFETY DESIGNS 大安全設計·為安心使用加分



29.7 cr

Reference Value 參考值

創新外型設計 Innovative Product Design

表面採用鏡面玻璃材質,視覺上放大浴室空 間。簡約平面設計,方便日常清潔,既實用 又美觀。產品設計榮獲德國iF設計大獎專利。

The design of sleek glass surface is easy

設有兩色發光面板 Lighting Function

設有柔和發光面板,有黃光和白光選擇, 可因應個人需要調較。

A hidden lighting system lights up your



智能溫度和濕度監測 Auto Temperature and Humidity Detector

示於遙控器上。





暖風功能 Instant Warming

暖風功能為你和家人帶來一個舒適的沐浴環境,不會 因應天氣的轉變而擔心著涼生病,特別適合家中有小 孩,孕婦及老人使用。它使用PTC陶瓷發熱,可快速 供暖,制熱效能較佳。在10分鐘內將室內溫度提升约 攝氐10℃。

隱藏式出風口設計,具有自動擺動及固定風向兩種模 式可供調節,可全方位供暖。








預設時間 Timer

預設時間功能。



換氣功能

換氣功能可把蒸氣換走,令浴室不再煙霧 瀰漫。設有高效換氣(6小時) 與節能換氣 (24小時)兩種模式,有效將空氣淨化去除 異味。



○ 乾衣功能

設有冷熱風循環乾衣功能。型號 K-77315T-MZ可於短短1.5小時 內把3.5公斤的濕衣烘乾;型號 K-77316T-MZ則需約2.5小時。



產品參資料

型號	電壓/頻率	額定輸入功率	熱風功能	涼風功能	干燥功率	換氣功率	空氣淨化功率	照明功率	照明輸入電流	換氣風量	換氣噪音	防護等級
Model	Voltage / Frequency	Rated Input Power	Heater Power	Fan Power	Dry Clothing Power	Ventilation Power	Air-care Power	Lighting Power	Lighting Input Volumn	Ventilation Volum	Ventilation Noise	Ingress Protection
K-77315T-MZ	220V~ /50Hz	2650W	2638W	30W	2650W (熱/ Hot) 55W (涼/ Cool)	25W	30W	12W	300mA	2.7m³/min	39dB	IPX2 (浴室寶 / Bathroom Heater) IPX4 (遙控 / Remote)
K-77316T-MZ	220V~ /50Hz	2150W	2140W	30W	2130W (熱/ Hot) 30W (涼/ Cool)	30W	30W	10W	300mA	2.2m³/min	43dB	IPX2 (浴室寶 / Bathroom Heater) IPX4 (遙控 / Remote)

KOHLER.HK

版權所有, 翻印必究。 2019 Copyright Reserved. ©All rights reserved by KOHLER Co.


產品概況 **SPECIFICATIONS**

K-77315T-MZ \$4,490



K-77316T-MZ

\$3,450



Unit: mm 單位: 毫米

如有任何爭議KOHLER 保留最終決定權。產品資料如有變更,恕不另行通知。 In the event of any dispute, KOHLER's decision shall be final and conclusive. Technical data subject to variant without notice.